

SPECIFICATION SHEET: S063

SYSTEM 1300z ZLocker TWO COMPARTMENT LOCKER



Dimensions:

Height	Width	Depth
1775 mm	400 mm	450 mm

Strength and Security with Style

Sturdy Construction	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength	Manufactured from 10mm thick solid grade laminate or compact density fibreboard in a plant on style. Supported by two unsprung 'five knuckle' semi-concealed hinges giving 180° door opening.
Style	Attractive and functional locker design.
Colour	We have a wide range of modern colours and finishes available from several leading manufacturers in the UK, please ask for details from the sales department.

Detailed Product Specification

Nesting:	Lockers are supplied as single units.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel-stove enamelled (see Finish specification).
Door Frame Assembly:	Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements.
Doors:	Solid grade laminate or compact density fibreboard doors are attached to the right and left hand side of door frame upright with two unsprung semi-concealed hinges to keep the door closed.
Bottom:	The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and rear edges drilled for fitting to stands or stands with seat.
Hook & Hanger Rails:	A coat hook is located each side of the each compartment.
Locking:	Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm).



Colour Range:	We have a variety of finishes and colours from several leading manufacturers, please ask for details from our sales department.
OPTIONAL EXTRAS:	The following can be supplied at an additional cost and, if included, will be specified in the quotation.
Combination Lock:	The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes, which can be reset.
Refund/Collect Lock:	Coin operated ASSA lock optionally available. This lock option is suitable for wet or dry area use. It's master keyed, user access by key on pin or wristband using coin or token specified. Accepts most European coins.
Locker Numbering:	a) Each compartment can be supplied with a plastic oval number plate recessed into the door centrally positioned at the top of the door. Maximum amount of digits is 4. b) Each compartment can be supplied with a number engraved into the door centrally positioned at the top of the door. Maximum amount of digits is 4.
Stands/Stand with Seats:	Lockers can be provided with either stands or stands with seats with or without adjustable feet. Please refer to Specification Sheet S015.
Sloping Tops:	Lockers can be manufactured with a sloping top. Gradient 1:3.
End Panels:	For aesthetic appearance and to protect row ends, specifically designed end panels are available.
Installation:	We offers a full installation service for its products.

Bespoke: We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

After-sales Service: All of our products are supported by our Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 749211 or email service@totallocker.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

