# **SPECIFICATION SHEET: S063**

## SYSTEM 1300z Z Locker TWO COMPARTMENT LOCKER





#### **Dimensions:**

HeightWidthDepth1775 mm400 mm450 mm

### Strength and Security with Style

Sturdy Construction Door Strength Door frame constructed from heavy gauge mild steel of press formed channel section. Manufactured from 10mm thick solid grade laminate or compact density fibreboard in a plant on style. Supported by two unsprung 'five knuckle' semi-concealed hinges giving  $180^{\circ}$  door

opening

Style Attractive and functional locker design.

Colour We have a wide range of modern colours and finishes available from several leading

manufacturers in the UK, please ask for details from the sales department.

## **Detailed Product Specification**

Nesting: Lockers are supplied as single units.

Construction: Spot welded and pop riveted.

Material & Finish: Mild steel-stove enamelled (see Finish specification).

Door Frame Assembly: Comprising two uprights manufactured from heavy gauge mild steel of press formed channel

section. Spot welded construction produces a rigid frame enabling door clearances to be

maintained in accordance with British Standard requirements.

Doors: Solid grade laminate or compact density fibreboard doors are attached to the right and left

hand side of door frame upright with two unsprung semi-concealed hinges to keep the door

closed.

Bottom: The bottom is formed as a 60 mm high plinth. All edges have return bends and the front and

rear edges drilled for fitting to stands or stands with seat.

Hook & Hanger Rails: A coat hook is located each side of the each compartment.

Locking: Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each

lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank

dimensions 6 mm). Recommended padlocks are available from TLS.

Colour Range: We have a variety of finishes and colours from several leading manufacturers, please ask for

details from our sales department.

**OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the

quotation.

Combination Lock: The standard cam lock or latch lock can be replaced with a door-mounted combination lock

with master key over-ride facility and user codes, which can be reset.

Refund/Collect Lock: Coin operated ASSA lock optionally available. This lock option is suitable for wet or dry area

use. It's master keyed, user access by key on pin or wristband using coin or token specified.

Accepts most European coins.

Locker Numbering: a) Each compartment can be supplied with a plastic oval number plate recessed into the door

centrally positioned at the top of the door. Maximum amount of digits is 4.

b) Each compartment can be supplied with a number engraved into the door centrally

positioned at the top of the door. Maximum amount of digits is 4.

Stands/Stands with Seats:

Lockers can be provided with either stands or stands with seats with or without adjustable

feet. Please refer to Specification Sheet S015.

Sloping Tops: Lockers can be manufactured with a sloping top. Gradient 1:3.

End Panels: For aesthetic appearance and to protect row ends, specifically designed end panels are

available.

Installation We offers a full installation service for its products.